NCCCO has established specific safety conditions and guidelines that each practical exam must follow. This Crane Report is a verification tool used to ensure that all testing parameters are within strict, safe working conditions. Before testing is conducted, the crane being used for testing must have its own unique report filled out. This report should be completed in ink, signed by the Examiner, and sent with the Site Report to: NCCCO—Testing Services Department, 1960 Bayshore Blvd., Dunedin, FL 34698.

Reminder: Each crane used must have a separate report filled out.

TEST SITE NUMBER			DATE	
NAME OF TEST SITE COORDINATOR			<u>'</u>	
NAME OF PRACTICAL EXAMINER				
CRANE OWNER/COMPANY NAME				
CRANE OWNER/COMPANY POINT OF CONTACT			PHONE NUMBER	
MAKE & MODEL OF CRANE		SERIAL NUMBER	3	
MAX. RATED CAPACITY (LB.)	MAX. BOOM RADIUS (FT.)		IS CRANE EQUIPPED WITH AUXILIARY STABILIZERS?	□ NO
MAIN STABILIZER SPREAD (FT.)		AUXILIARY STAE	BILIZER SPREAD (FT.)	
TEST SITE LAYOUT USED:				
☐ ABC #1: Boom Radius 22–30 ft.				
If using ABC #1, provide next load c BOOM RADIUS (ft.)	hart rating beyond 22 ft.: CAPACITY (lb.)		MAXIMUM ALLOWABLE LOAD WEIGHT	
	•	x .75	<b>=</b> LB.	
☐ ABC #2: Boom Radius 30 ft. or greater;	Auxiliary Stabilizer span less than	14 ft. (if equipped)		
If using ABC #2, provide next load of BOOM RADIUS (ft.)	hart rating beyond 30 ft.: CAPACITY (lb.)		MAXIMUM ALLOWABLE GROSS WEIGHT	
	•	x .75	<b>=</b> LB.	
☐ ABC #3: Boom Radius 34 ft. or greater;	Auxiliary Stahilizer span 14–32 ft	(must be equipped)		
If using ABC #3, provide next load c BOOM RADIUS (ft.)	·	(mase se equipped)	MAXIMUM ALLOWABLE LOAD WEIGHT	
	•	x .75	<b>=</b> LB.	
Note: Gross Load (Test Weight+Rigging) used must be less than Maximum Allowable Load Weight calculated above.		GROSS LO USED IN TESTI	ID	
I attest that this is a true and accura	te report of the crane and a		r used for testing. CCREDITATION # DATE	